



TRYGG

Preferred for a reason



Tractor

Mounting instruction

911002



1. Legg kjettingen bak dekket med piggene opp og låsene mot dekket. Heng kjettingen fast i dekkets mønster. Kjør fremover og la kjettingen legge seg på.

1. Lay the chain down behind the tire with studs pointing upwards and the locks facing the tire. Fasten the chain to the tire and drive the chain on.



2. TRAKTOR har en demonterbar seksjon i enden. Denne fjernes ved behov. Visse tilfeller kan det være nødvendig å kappe vekk ytterligere kjetting ved montering (markert med rødt på bilde 1).

2. TRACTOR has a removable end section. Removed this if necessary. In certain cases, it may be necessary to cut away additional chain during assembly (marked in red in the picture no. 1).



3. Når kjettingen er ferdig montert etterjusteres evt. lengde og stramming på sidekjettingen og plasseringen av sidestroppene som er festet med sjakler. Ferdig justert skal sidestroppene peke mest mulig rett inn mot dekkets sentrum. Evt. overflødig kjetting festes eller kappes vekk.

Det er viktig at TRAKTOR monteres med relativt god stramming, dog ikke så stramt at kjettingens vandring på dekket hindres.

3. When the chain is mounted, it may be necessary to do some readjustments on the side chain and on the shackle fastened side straps. All side straps should point towards the centre of the rim.

The TRACTOR should be mounted relatively tight, but not so tight that the chains' natural movement on the tire is obstructed.

Thank you for choosing TRYGG!

TRYGG (Norwegian for “safe”) is a name that commits. Since 1939, we’ve pushed product development and innovation to deliver the safest and most user-friendly products.

Our sourcing and production methods ensure some of the world’s most environmentally friendly chains.

We hope you enjoy your new TRYGG tire chains!



WARNING!

**IMPROPER USE CAN RESULT
IN DEATH OR SERIOUS INJURY**

*ONLY use these chains as tire chains.
NEVER use for towing, lifting, securing,
or lashing.*

*DO NOT exceed 30 mph (50 km/h).
Chains can break under tension
causing hazardous projectiles and
loss of vehicle control.*

*DO NOT operate with worn, damaged,
or improperly installed chains.*

*DO NOT use tire chains on dry pavement
or under conditions where snow or ice
is not present, as this may cause tire
damage or loss of control.*

*ALWAYS read and follow full safety
instructions provided in the QR-code
link.*

Information
regarding use,
safety and warranty:



User manuals
in more languages:



www.trygg.no

www.nosted.com