

Rundslingskobling type YM

QR Code

Teknisk data

| Varenr | Type.Code | WLL | For kjetting | K | Mål i mm | | | KG |
|----------|-----------|-------------|-----------------|-----|----------|----|----|------|
| | | | | | W | A | B | |
| | | 4:1 tonn | | | | | | N.W. |
| 0210120 | YW-7/8 | 2,00 | 7/8 mm | 33 | 40 | 18 | 24 | 0,2 |
| 0210121 | YW-10 | 3,15 | 10 mm | 42 | 47 | 25 | 29 | 0,4 |
| 0210122 | YW-13 | 5,30 | 13 mm | 51 | 53 | 30 | 35 | 0,7 |
| 0210123 | YW-16 | 8,00 | 16 mm | 63 | 67 | 36 | 44 | 1,3 |
| 0210124 | YW-18/20 | 12,50 | 18-20 mm | 71 | 80 | 42 | 52 | 2,1 |
| 0210125* | YW-22 | 15,00 | 22 mm | 112 | 125 | 49 | 72 | 5,7 |
| 0210126* | YW-26 | 21,20 | 26 mm | 130 | 150 | 55 | 84 | 9,0 |
| 0210127* | YW-32 | 31,50 | 32 mm | 165 | 190 | 69 | 85 | 14,0 |



Rundslingskobling type YM

Produktbeskrivelse

- Design faktor 4:1 testet and sertifisert i henhold til NS-EN 1677-1