

Kortlenket kjetting G80 NS- EN 818-2



QR Code



Varenr.	Produkt ID	WLL		Prøvelast		MBL		Dimensjoner (mm)			Vekt (kg/m)
		tonn	kN	tonn	kN	tonn	kN	D	L	B	
0101100	6x18	1.12	11.0	2.9	28.3	4.6	45,2	6	18	8.0	0.8
0101102	8x24	2.0	19.6	5.1	50.3	8.2	80,4	8	24	11.4	1.4
0101103	10x30	3.15	30.9	8.0	78.5	12.8	126	10	30	14.0	2.2
0101104	13x39	5.3	52.0	13.6	133	21.6	212	13	39	18.2	3.8
0101105	16x48	8.0	78.5	20.5	201	32.8	322	16	48	22.4	5.7
0101106	20x60	12.5	122.6	32.0	314	51.3	503	20	60	28.0	8.6
0101107	22x66	15	147.2	38.7	380	62.0	608	22	66	29.0	10.9
0101108	26x78	21.2	208.0	54.1	531	86.5	849	26	78	33.8	15.2
0101109	32x96	31.5	309.0	82.0	804	131.2	1287	32	96	42.0	23.0

Kortlenket kjetting G80 NS- EN 818-2



Kortlenket kjetting til løfteformål. Sertifisert iht. NS-EN 818-2.