

GANTERUD L12 Pro



QR Code

Technical data

Technical Data	
Lifting Capacity	Max. 12 tons
Leveling Force	Max. 2,5 tons
Max. Leveling Stroke Length	4 m (1.5 m in both directions) in the standard version
Two Leveling Speeds	
Max. Chain Angle	60 degrees at 12-ton load
Total Chain Length	4 m in the standard version
Chain Dimensions	48 x 16 mm
Weight	Approx. 295 kg (including chains and hooks)
Height	750 mm
Width	740 mm
Depth	595 mm

Control System	
Radio Range	100 m (line of sight)
Electric Motor Voltage	24 V DC
Power Consumption, Standby	50 mA
Power Consumption, Max. Continuous	24 A
Power Consumption, Peak	30 A

Certification

CE-marked product

Environmental Requirements	
Operating Temperature	-20 °C til +40 °C
Storage Temperature	-20 °C til +45 °C



Relative Humidity (RH)

0–90 % during storage

GANTERUD L12 Pro



Product description

GANTERUD L12 is a lifting yoke that combines new and proven technology to ensure precise, safe, and efficient load leveling.

With a capacity ranging from 0 kg to 12 tons, it can handle both light and heavy objects with high precision. It features a reversible stroke length of up to 4 meters per hook and can be adjusted to two speeds for optimal control.

Designed for demanding work environments, the **L12 Pro** operates in temperatures from -20 to $+40$ °C. Its robust construction, combined with an IP65-rated electrical system, ensures high durability and easy cleaning. With an IP67-classified remote control, the L12 Pro provides the user with seamless and reliable control. Under normal use, the battery only needs charging once per week, minimizing maintenance and maximizing productivity.